



## Release Notes

# hp StorageWorks Tru64 UNIX Kit for Enterprise Virtual Array

**Product Version:** 3.0d

Third Edition (May 2004)

**Part Number:** AV-RUGSC-TE

This document contains the most recent product information about the HP StorageWorks Tru64 UNIX Kit v3.0d used for integrating host servers with the StorageWorks Enterprise Virtual Array (VCS version 3.014).

For the latest version of the Tru64 Release Notes and other documentation, access the HP storage web site at <http://www.hp.com/country/us/eng/prodserv/storage.html>.





---

© Copyright 2001–2004 Hewlett-Packard Development Company, L.P.

Hewlett-Packard Company makes no warranty of any kind with regard to this material, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Hewlett-Packard shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

This document contains proprietary information, which is protected by copyright. No part of this document may be photocopied, reproduced, or translated into another language without the prior written consent of Hewlett-Packard. The information contained in this document is subject to change without notice.

Compaq Computer Corporation is a wholly-owned subsidiary of Hewlett-Packard Company.

Hewlett-Packard Company shall not be liable for technical or editorial errors or omissions contained herein. The information is provided “as is” without warranty of any kind and is subject to change without notice. The warranties for Hewlett-Packard Company products are set forth in the express limited warranty statements for such products. Nothing herein should be construed as constituting an additional warranty.

Printed in the U.S.A.

HP StorageWorks Tru64 UNIX Kit for Enterprise Virtual Array Release Notes  
Third Edition (May 2004)  
Part Number: AV-RUGSC-TE



## About this document

This section describes the content reflected in this document, including:

- [Release Notes information](#), page 3
- [Intended audience](#), page 4

## Release Notes information

These release notes cover the following major topics:

- [Enterprise Virtual Array storage system](#), page 5
- [Supported operating systems](#), page 6
- [Avoiding problem situations](#), page 8
- [Enterprise Storage System notes](#), page 9
- [Storage System Scripting Utility for Enterprise Virtual Array](#), page 10



## Intended audience

This document is intended to assist customers who purchased the StorageWorks Enterprise Virtual Array and the associated StorageWorks Operating System kits. Other associated software packages are:

- StorageWorks Virtual Controller Software Package v3.014 for Dual HSV Controllers
- StorageWorks Snapshot for Virtual Controller Software v3.014 for Dual HSV Controllers

This document is also intended for use by HP Customer Service personnel responsible for installing and maintaining designated devices associated with this storage system.

## Conventions

The following conventions are used throughout this document:

- Unless otherwise specified, all references to VCS v3.014 refer to the software package (kit) and documentation version level. These software packages and documentation support VCS v3.014.
- *The System Software for Enterprise Virtual Array* is the storage system software that contains Virtual Controller Software (VCS), Environmental Monitoring Unit (EMU) firmware, programmable component images, diagnostics, and message files. This storage system software is usually represented by a four-digit number, for example v3.014.
- Unless otherwise specified, all references to an HSV110 controller or an HSV110 controller pair should be interpreted as the HSV110 or HSV100 controller or controller pair.
- Unless otherwise specified, all references to the Enterprise Storage System or storage system should be interpreted as the EVA5000 or the EVA3000.
- Unless otherwise specified, all references to rack should be interpreted as the 9000-Series Enterprise Storage System Rack.
- Unless otherwise specified, all licensing references to host ID should be interpreted as the storage system World Wide Name (WWN).
- Unless otherwise specified, all references to the management appliance should be interpreted as the HP StorageWorks Management Appliance.
- Unless otherwise specified, all references to a single instance of a management agent should be interpreted as the HP StorageWorks Command View EVA.
- The term Fabric means Fibre Channel Switched (FC-SW) connectivity.

## New features

This section briefly describes new features and changes that are supported by the version 3.0d release of the Platform Kit together with the array controller running VCS version 3.014.

### New features for version 3.0d

The following are major enhancements included in the v3.0d release of the Platform Kit:



## Enterprise Virtual Array storage system

This document contains the most recent product information about the Enterprise Virtual Array. An Enterprise Virtual Array storage system consists of the following:

- One pair of HSV110 controllers.
- An array of physical disk drives that the controller pair controls. The disk drives are located in drive enclosures that house the support systems for the disk drives.
- Associated physical, electrical, and environmental systems.
- Command View EVA, which is the graphical interface to the storage system. Command View EVA software resides on the Management Appliance and is accessed through a browser.
- Management Appliance, switches, and cabling.
- At least one host attached through the fabric.

## Enterprise Virtual Array system software

HP StorageWorks Virtual Controller Software (VCS) v3.014 provides storage software capability for the HSV110 Array Controller and is provided in the VCS v3.014 software kit.

## Multiple storage system types

The extended interoperability of the heterogeneous SAN allows you to mix several types of HP StorageWorks storage systems. For more information about configuration rules, refer to the *HP StorageWorks SAN Design Reference Guide* at <http://h18000.www1.hp.com/products/storageworks/san/documentation.html>

## Enterprise Virtual Array documentation

The Enterprise Virtual Array Catalog of Associated Documentation is included on the Technical Documentation page. You can display a comprehensive list of Enterprise Virtual Array documentation as well as associated product documentation that may be required to operate your storage system. To access the Technical Documentation page, go to <http://h18006.www1.hp.com/products/storageworks/enterprise/documentation.html>

## Supported configurations

Refer to the Enterprise Virtual Array Quick Specs for supported configurations. The *HP StorageWorks SAN Design Reference Guide* is a detailed guide for SAN configurations and is available at <http://h18004.www1.hp.com/products/storageworks/san/documentation.html>



## Supported operating systems

The Enterprise Virtual Array storage system is compatible with the following operating systems:

- Tru64 UNIX
- Windows NT/Windows 2000/Windows Server 2003 (32- and 64-bit)
- OpenVMS
- Sun Solaris
- HP-UX
- IBM AIX
- Linux
- Novell NetWare

Table 2 lists the operating system's specifications, which are compatible with the Enterprise Virtual Array.

---

**Note:** Table 2 contains current minimum level operating system specifications at the time of the Enterprise Virtual Array v3.014 release. Some component versions may change due to revision. For the latest information, go to:

<http://h18006.www1.hp.com/storage/index.html>

---

**Table 1: Operating system specifications**

Platform	OS version	Clustering	FCA (HBA)	Adapter firmware
Tru64 UNIX	5.1 (PK6)	TruClusters	DS-KGPSA-C A	3.91a1
			DS-KGPSA-D A	3.91a1
			DS-KGPSA-EA	1.00x8
	5.1A (PK4)	TruClusters	DS-KGPSA-C A	3.91a1
			DS-KGPSA-D A	3.91a1
			DS-KGPSA-EA	1.00x8
	5.1B (PK2)	TruClusters	DS-KGPSA-C A	3.91a1
			DS-KGPSA-D A	3.91a1
			DS-KGPSA-EA	1.00x8



## Switch support

**Note:** This Fibre Channel Platform Kit supports the Fibre Channel switches and firmware versions listed in the *HP StorageWorks SAN Design Reference Guide* at <http://h18000.www1.hp.com/products/storageworks/san/documentation.html>. HP recommends that you do not mix switch firmware versions in your SAN. It is considered best practice to uniformly upgrade all switches in the SAN.

## Multiple path support

Tru64 UNIX requires no additional software for high availability multiple path capability. Using multiple paths is integrated into recent releases of these operating systems.

## Single path support configurations

Tru64 UNIX servers with a single FCA supports single path mode.

**Note:** Single path mode should not be used in mission critical environments.

## Supported Alpha servers

Table 3 lists the Enterprise Virtual Array compatible Alpha servers.

**Table 3: Supported Alpha servers**

Product	Maximum number of FCAs/Alpha system			
	Tru 64 UNIX switch		OpenVMS switch	
	Single	Cluster	Single	Cluster
AS800	2	2	2	2
AS1200	4	4	4	4
AS4100	4	4	4	4
AS4000	4	4	4	4
AS8200	64	32	26	26
AS8400	64	32	26	26
DS10	2	2	2	2
DS15	2	2	2	2
DS20	4	4	4	4
DS20 E	4	4	4	4
DS25	4	4	4	4
ES40	4	4	4	4
ES45	4	4	4	4
ES47	24	24	24	24
ES80	24	24	24	24
GS60	64	32	26	26



**Table 3: Supported Alpha servers (Continued)**

Product	Maximum number of FCAs/Alpha system			
	Tru 64 UNIX switch		OpenVMS switch	
	Single	Cluster	Single	Cluster
GS80	64	32	26	26
GS160	64	32	26	26
GS320	64	32	26	26
GS140	64	32	26	26
GS1280	32	32	32	26

## Operating constraints

Any operating constraints specific to the Enterprise Virtual Array hardware and Command View EVA can be found in their respective release notes.

## Failover/failback

There are specific failback preference settings for the HSV controllers that are operating system specific (refer to the Enterprise Virtual Array hardware release notes for details).

## Avoiding problem situations

The following sections list problems that may arise during platform kit operation and how to avoid those problems.

### Command View EVA

Information about avoiding problem situations specific to Command View EVA can be found in the Command View EVA release notes.

### Enterprise Virtual Array version 3.014 hardware

Information about avoiding problem situations pertaining to Enterprise Virtual Array hardware can be found in the hardware release notes in your VCS kit.

## Codeload usage

When a maximum configured system is running at maximum load, codeload functionality cannot be used effectively due to Secure Path timing constraints. The system may time out before codeload is completed. Because of this behavior, VCS upgrade should be done during off peak usage.



## Avoiding problem situations with the SSSU

### Changing comments on a disk enclosure

You cannot use the SSSU to change comments on a disk enclosure. To avoid this situation, use Command View EVA to change comments on a disk enclosure. If you try to change a disk enclosure comment in the SSSU, the following error message appears:

```
Error: Invalid Operation
```

### Changing the name of a disk enclosure

Changing the name of a disk enclosure is not supported with the SSSU or with Command View EVA. If you try to change a disk enclosure name in the SSSU, the following error message appears:

```
Error: Invalid Operation
```

## Upgrading the runtime libraries on Tru64 v5.1

On Tru64 v5.1, the C++ runtime libraries need to be upgraded. This can be done by installing the kit located in the `cxxruntime` directory on the Tru64 v3.0D Kit CD-ROM.

Untar this file into an empty directory and use the following command to install the libraries.

```
tar xf CXXREDIST632V18.tar
setld -l ./CXXREDIST632.kit
```

## Enterprise Storage System notes

### Cable requirements

When an Enterprise Virtual Array is connected to a 1Gb switch an SC-to-LC cable is required for host connectivity. [Table 4](#) and [Table 5](#) provide listings of available cables.

**Table 4: LC-SC cables**

Length	Description	HP part number
2.0 m ± 40 mm	CA ASSY, LC-SC, Optical 2M	187891-002
5.0 m ± 80 mm	CA ASSY, LC-SC, Optical 5M	187891-005
15.0 m ± 150 mm	CA ASSY, LC-SC, Optical 15M	187891-015
30.0 m ± 300 mm	CA-ASSY, LC-SC, Optical 30M	187891-030
50.0 m ± 500 mm	CA-ASSY, LC-SC, Optical 50M	187891-050



**Table 5: LC-LC cables**

Length	Description	HP part number
2.0 m ± 40 mm	2-meter LC-LC Multi-Mode Fibre Cable	221692-B21
5.0 m ± 80 mm	5-meter LC-LC Multi-Mode Fibre Cable	221692-B22
15.0 m ± 150 mm	15-meter LC-LC Multi-Mode Fibre Cable	221692-B23
30.0 m ± 300 mm	30-meter LC-LC Multi-Mode Fibre Cable	221692-B26
50.0 m ± 500 mm	50-meter LC-LC Multi-Mode Fibre Cable	221692-B27

## Storage System Scripting Utility for Enterprise Virtual Array

Refer to the *Command View EVA Release Notes* prior to using the Storage System Scripting Utility (SSSU), as SSSU communicates directly with the Command View EVA.